

OSC 02NC108 Ultrasonic Scaler

<Features>

- ULTRASONIC FREQUENCY: ~ 30 KHz
- Aerodynamic style, compact size and light weight.
- “Endo” function possible at low power with additional attachment.
- Smaller handpiece and smaller Inserts.
- State of the art Circuitary.
- Optimum Power & Automatic tuning on all load conditions
- Tough & Rugged.



<Standard Accessories>

- Power Supply Unit with cord.
- Foot control.
- Water tube.

<Optional Accessories>

- Magnetic Tips
- Water Booster
- Water Filter

<Specifications>

| Model | OSC 02NC 108 |
|--------------|---|
| Dimension | Approx. 180x140x40 mm |
| Weight | Approx. 3.5kg (with power supply) |
| Power Rating | Main Voltage : 240 ~ 220Volts, 50Hz. Wattage : Approx. 35 Watts. Water Pressure: 15 to 20 PSI. |

OSC 02NC109/110 Ultrasonic Scaler

<Introduction>

-Latest piezoelectric ultrasonic scaler:
 “OSC 02NC 109”. Reap the benefits of powerful Piezoelectric technology with state-of-the-art control module circuitary.
 The OSC Piezomatic provides the best performance with real-time adjustment of optimum power to the tips which means smooth & constant vibrations during treatment.

<Features>

- ULTRASONIC FREQUENCY: 26 ~ 30 KHz
- Aerodynamic style, compact size and light weight.
- “Endo” function possible at low power with additional attachment.
- Smaller handpiece and smaller Inserts
- State of the art Circuitary.
- Optimum Power & Automatic tuning on all load conditions.
- Tough & Rugged.



<Specifications>

| Model | OSC 02NC 109 | OSC 02NC 110 |
|----------------|--|---------------------|
| Dimension | Approx. 140x140x40 mm | |
| Weight | Approx. 3.5kg (with power supply) | |
| Power Rating | Main Voltage : 240 ~ 220Volts, 50Hz. Wattage : Approx. 35 Watts. | |
| Compatible tip | EMS** type tips | SATELAC** type tips |

**Regd. Trademark of respective companies