

## OSC 02OT101 Washer Disinfecter

### <Features>

- It can handle as many as 1280 instruments per hour
- Advanced microprocessor which controls all services, programming and statistic functions
- Effective cleansing
- Circulated water can be heated by either electricity or steam
- Purified water rinse
- Effective drying

### <Specifications>

<b>Model</b>	<b>OSC 02OT 101</b>
Floor dimension	Approx. 780x700 (WxD) mm
Height	Approx. 1,530 mm



## OSC 02OT102 Sterilizer

### <Features>

- Available in 2 pressure types ( Standard/High speed)
- Pressure switches for economic power consumption
- Self locking safety door under pressure and heat resistant EPDM door gasket

### <Specifications>

Model	Capacity(L)	Chamber Diameter · depth	Steam Generator Capacity (L/kW)
OSC 02OT 102A	79L	Approx. 400x600mm	45/18 (l/kw)
OSC 02OT 102B	186L	Approx. 500x900mm	69/36 (l/kw)
OSC 02OT 102C	79L	Approx. 400x600mm	26/6 (l/kw)
OSC 02OT 102D	145L	Approx. 400x1100mm	44/9 (l/kw)
OSC 02OT 102E	186L	Approx. 500x900mm	44/9 (l/kw)
OSC 02OT 102F	227	Approx. 500x1100mm	44/9 (l/kw)
OSC 02OT 102G	267L	Approx. 600x900mm	44/9 (l/kw)
OSC 02OT 102H	511L	Approx. 750x1,100mm	80/18 (l/kw)



## OSC 02OT103 Sterilizer for Hospital & Pharmaceuticals

### <Features>

- Safe, efficient performance
- Environment-friendly operation
- The lowest water consumption levels
- Outstanding flexibility and operating simplicity
- Top quality modular stainless steel construction
- Prevalidated MICROSTER control system

### <Specifications>

Model	Capacity (L)	Chamber depth	Door opening
OSC 02OT 103A	185L	915mm	460x460mm
OSC 02OT 103B	564L	1,250mm	660x660mm
OSC 02OT 103C	1275L	1,525mm	915x915(horizontal) mm

