OSC 57FY105 Carbon Monoxide Meter



<Applications>

-The carbon monoxide meter detects the presence of carbon monoxide (CO),

and measures concentrations between 1 ~ 1,000 parts per million (PPM).

-The meter indicates the presence of carbon monoxide in two ways.

By a reading on the LCD in PPM

·By a beeper tone

-The meter indicates the presence of CO by a reading on the LCD and a beeper tone.

-The beeper functions much like clicking of a Geiger counter.

-Above 200 PPM, the beeper sounds continuously with the consentration of CO.

-From 35 PPM to 200 PPM, the beeper sounds constinuously with the concentration of CO.

<Features>

-Audio alarm

-Direct readout of CO concentration in parts per million, PPM.

<Specifications>

Model	OSC 57FY 105
Temperature range Operati	ng 0 to +50
Stora	ge -30 to +60
Operating humidity	0 ~ 99% Relative humidity (non-condensing)
Measurement range	0 to 1000PPM
Measurement resolution	1PPM
Accuracy	± 5% or ±10PPM
Warm up period	< 2 seconds
Battery	9V IEC 6LR61, or equivalent
Auto power off	Meter automatically shuts down
	after 15 minutes of inactivity
Sensor type	Stabilizes electrochemical gas specific CO