OSC 97AU114 Soil PH-Moisture Meter

- <Features>
- -Simple operation, can directly insert the soil

<Specifications>

Specifications/		
Model	OSK 97AU115-A	OSK 97AU115-B
Measuring pH range	3∼8 pH	
PH accuracy	±0.2pH	
Measuring moisture range	1~8%	
Moisture accuracy	±1%	
Environment temperature	5∼50°C	
Measuring depth range	60mm	20~300mm
Dimension(mm)	approx.160x90x60	approx.350x120x60
Weight	0.5kg	



OSC 97AU115 Portable Raw Leaf Area Meter

<Features>

-Can test the raw leaves area without damage.

<Specifications>

Model	OSC 97AU 115-A	OSC 97AU 115-B
Applicable Parameter	leaf area, average area, length of leaf, width of leaf, thickness of leaf, perimeter and ratio of Length to width.	
Length	1,000mm	
Width	160mm	
Thickness	≦8mm	
Stored data	200	
Interface (PC)		RS-232 link
Dimension (mm)	approx.280X90X50	
Weight	2kg	2.5kg
Power source	AA battery x 4	



OSC 97AU 115-A

OSC 97AU116 Portable Area Meter

<Features>

- -Can test farmland, green land, forest, water area, tidelands and so on regular & irregular area.
- -It can also test distance and perimeter
- -GPS function
- -OSC 97AU116-B can show the outline of the test area through the RS-232 link with complete the complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with complete state of the test area through the RS-232 link with the RS-232 link with complete state of the test area through the RS-232 link with the RS-23

<Specifications>

Model	OSC 97AU 116-B
Measuring range	0∼9,999,999m²
Accuracy	±3.0%
Measuring distance range	0∼999,999.9m
Measuring distance accuracy	2.0m(CEP)
Measuring unit	Meter, Meter square
Interface (PC)	RS-232 link
Stored data	128
Dimension (mm)	approx.250x180x100
Weight	2.5kg
Power source	AA battery x 4



OSC 97AU 116-A