

OSC 997KN005 Big size Hot Circulator Oven

<Features>

- Digital LED panel displays and controls the temperature. It also can work with SSR or replay method.
- 3 stages of heating switch control in order to reach great precision.
- Specially made high-temperature resist long shaft motor and louverd fan.
- Use forced convection to exhaust steam, waste gas and volatile gas, also dry rapidly.

<Applications>

- Reserch institution, school, factory, quality control, laboratory, electron, electric machinery, hardware, plastic, printing, GMP phaumaceutics, Chemical industry, Food products, Agricultural products, Art works, and Different kinds of roasting, Sterilizing, Pre-heat, Temper.



<Specifications>

Model	997KN005A	997KN005B	997KN005C	997KN005D	997KN005E	997KN005F	997KN005G
Interior (DxWxH) cm	90x60x50	100x100x60	100x120x60	120x140x60	140x160x80	140x180x100	160x200x120
Exterior (DxWxH)cm	150x82x65	158x105x75	158x145x75	182x165x75	205x190x95	205x210x116	225x230x135
Capacity	270L	600L	720L	1008L	1792L	2520L	3840L
Pailing*	5	6	6	7	8	8	9
Door	1	1	2	2	2	2	2
Temperature range	Room temperature ~200 or ~300						
Accuracy	0.5 spread 2						
Temperature controller	Digital LED panel displays and control the temperature						
Material	Inner: SUS430 Stainless steel plate Outer: Galvanized steel plate with finish.						
Control system	Adopt SSR method. Or replay method. 3 steps of heating						
Airflow method	Horizontal airflow louverd fan use forced circulation						
Attachments	Gravity-resist wheels on the foundation, easy to move around. Ampere meter						
Power supply**	220V,1φ	220V,1φ	220V,3φ	220V,3φ	220V,3φ	220V,3φ	220V,3φ
Current	4KW	7KW	8KW	11KW	14KW	19KW	25KW

* Number of palings can be added upon request

** 380V or 440V is available upon request