OSC 997ST009 Oil-free Compressor

<Features>

- Piston-powered, Oil-free pump
- Quiet and low vibration, noise level only 50dB.
- Aluminum die-cast and precise construction
- enabling its compact and small body - Clean and maintenace free

<Accessories>

- Moisture Trap, Vacuum regulator
- Repair kit (Option)
- <Consumables>
- Filter cartridge

<Applications>

- 1. Oxigen supply in the water
- 2. Agitation in ferment tank
- 3. Bubble test
- 4. Aeration test



OSC 997ST 009A



OSC 997ST 009B

| <specifications></specifications> | | | | |
|-----------------------------------|------------------|------------------|------------------|------------------|
| Model | OSC 997ST 009A | | OSC 997ST 009B | |
| Power Supply | AC110-120V, 60Hz | AC220-240V, 50Hz | AC110-120V, 60Hz | AC220-240V, 50Hz |
| Power consumption(W) | 90 | 85 | 147 | 125 |
| Max.current(A) | 0.9 | 0.4 | 1.51 | 0.6 |
| Max. pressure (psi) | 100 | 100 | 100 | 100 |
| without moisture trap (bar) | 6.9 | 6.9 | 6.9 | 6.9 |
| Max. pressure (psi) | 80 | 80 | 80 | 80 |
| with moisture trap (bar) | 5.5 | 5.5 | 5.5 | 5.5 |
| Max. Flowate(I/min) | 14 | 12 | 27 | 25 |
| Motor rotation (rpm) | 1700 | 1400 | 1700 | 1400 |
| Horse Power(HP) | 1/8. | 1/8. | 1/6. | 1/6. |
| Pole | 4P | 4P | 4P | 4P |
| Noise Level(dB) | 50 | 50 | 50 | 50 |
| Port Thread(inch) | 5/16" | 5/16" | 5/16" | 5/16" |
| Net Weight(kg) | 4.1 | 4.1 | 5.2 | 5.2 |

OSC 997ST010 Compressed Air Supply System

<Features>

- The system consists of a compressor, Strainless steel air tank and pressure regulator/moisture trap. Air is pumped into air tank by compressor, then goes through pressure regulator/ moisture trap. After regulating and filtrating, air goes to where you connect.

<Applications>

Filtered compressed air is employed for oxygen supply, aeration and agitation of the medium in many phamaceutical and biotechnological processes which need pressurized air or gas as a bacis requirement for optimized operation or cell growth. Such as fermentor, bioreactor

<Specifications>

| Model | OSC 997ST 010 | | | | |
|----------------------|------------------|------------------|--|--|--|
| Power Supply | AC110-120V, 60Hz | AC220-240V, 50Hz | | | |
| Power consumption(W) | 147 | 125 | | | |
| Max.current(A) | 1.51 | 0.6 | | | |
| Max. pressure | 60 | 60 | | | |
| Max. Flowate(I/min) | 27 | 25 | | | |
| Motor speed(rpm) | 1700 | 1400 | | | |
| Horse Power(HP) | 1/6 | 1/6 | | | |
| Pole | 4P | 4P | | | |
| Noise Level(dB) | 50 | 50 | | | |
| Port Thread(inch) | 5/16" | 5/16" | | | |
| Net Weight(kg) | 8.4 | 8.4 | | | |

<Accessories>

- Moisture Trap
- <Consumables>
- Filter cartridge

